

## Operating Instructions

Number: 04- 010  
Subject: Mezzanine Deck  
Date of Issue: 15/11/2004

# Freighter Mezzanine Deck Operating Instructions

### DISCLAIMER:

These instructions are provided by MaxiTRANS Australia Pty Ltd (MaxiTRANS) for the purposes of assisting with the operation, repair or servicing of your Freighter or Maxi-CUBE trailer. Operation, repair or servicing of your Freighter or Maxi-CUBE trailer should only be undertaken by a person who has appropriate professional training and suitable qualifications. You are wholly responsible for ensuring that an appropriately qualified person is engaged to undertake the proposed work in respect of the Freighter or Maxi-CUBE trailer in a safe and diligent manner and with all appropriate equipment.

To the maximum extent permitted by law, MaxiTRANS, and its related entities, directors, other officers, employees, advisers and agents, will not be liable in any way for any direct, indirect or consequential loss, damage, expense, injury or claim of whatever description arising from or relating to the application or use of these instructions.

MaxiTRANS may amend or replace these instructions at any time without notice. Please refer to the MaxiTRANS web site ([www.maxitrans.com.au](http://www.maxitrans.com.au)) for the latest version.

The platform second decks are designed to increase the carrying capacity of the trailer by providing a deck space that is adjustable in height to suit the load. The deck may be loaded with pallets or similar freight that uniformly loads the floor up to the placarded load capacity of the deck.

To change the deck height a forklift of 1500kg capacity or greater is required and the trailer must be on a smooth level surface.

1/ Insert the fork tynes into the fork pockets of the deck as far as possible.



2/ Lift the deck off the deck saddles.

3/ Remove the deck saddles by lifting and tilting out of the post.



4/ Relocate the saddles to the required position, ensuring that the saddles are each positioned at the same height using the numbers on the posts as a guide.

5/ Lower the deck onto the saddles ensuring each corner of the deck correctly engages into the saddles.



**CAUTION:**

1): To prevent damage, the decks and gates, if fitted, must be restrained by a winch strap or similar device when travelling unladen.

2): Take care that fingers or hands are not trapped and injured when lowering the decks on to their saddles.

3): Prior to refitting the decks after removal, regularly inspect the saddles for cracks or significant damage. It is recommended that new saddles be purchased rather than carrying out repairs on damaged or cracked saddles.